

Each information

| Depth | 27.2" |
|---------------|--------------|
| Width | 16.6" |
| Height | 11.2" |
| Gross weight | 37.30lb |
| UPC# | 033816032163 |
| Unit quantity | 1 |

Case information

| Depth | 27.2" |
|---------------|--------------|
| Width | 16.6" |
| Height | 11.2" |
| Gross weight | 37.05lbs |
| UPC# | 033816032163 |
| Unit quantity | 1 |

Shipping Information

| Country of origin | KR |
|------------------------|------|
| Minimum Order Quantity | 1 |
| Lowest possible unit | Each |

General information

1700300 Moore # **Recycled %**

GBC Professional HeatSeal H600 Pro Thermal Pouch Laminator, 13" Max Width, 1.5 - 10 Mil

1700300

Product Description

H600 Pro pouch laminator uses 4 heated rollers to provide professional lamination results. Easy to use keypad control panel with LCD readout. Accepts documents up to 13" wide. Laminates pouches 1.5 to 10 mil.

Features

- Meet all of your laminating needs with one machine. The sturdy metal housing is designed for durability and lasting ٠ performance. Perfect for frequent use and a wide range of projects.
- Get started on projects right away. The laminator warms up in 4-8 minutes for quick and easy use, and laminates at speeds up to 25" per minute.
- With 4 smooth rollers, your documents will stay bubble and wrinkle-free. Compatible with any laminating pouches from 1.5 to 10 mil and mounting boards up to 2mm.
- The wide 13" document width is great for a larger variety of projects, such as banners, menus and certificates. Comes with 1 year warranty to ensure your satisfaction.
- · Lamination made simple. The touch button interface with LCD display allows for quick adjustments to temperature and speed, while the reverse switch quickly clears jams.
- A cold lamination setting provides more laminating options. Cold lamination works with pressure-sensitive adhesive
 pouches including GBC SelfSeal pouches, sold separately.

Specifications

- Color White
- Detailed Color lvory
- Film Type Pouch
- Material Metal

0

- Warranty Limited 1-year
- Thickness (mil) Up to 10 mil
- Warm-up time (minutes) 4-8



